




EN50155 Compliant Product Offerings

	Network Cameras			
	 MD8531H	 MD8562/62D	 FE8174V	 FE8181V
Frame per Second	30 fps @ 1280x960	30 fps @ 1920x1080	15 fps @ 1920x1920 30 fps @ 1920x1080	15 fps @ 1920x1920 30 fps @ 1920x1080
IR Illuminators	-	-	-	10 m IR
Video Compression	H.264, MJPEG & MPEG-4	H.264, MJPEG & MPEG-4	H.264, MJPEG & MPEG-4	H.264, MJPEG & MPEG-4
Audio Capability	Two-way Audio	Audio In	Two-way Audio	Two-way Audio
3DNR	√	-	-	√
WDR	WDR Pro	WDR Enhanced	WDR Enhanced	WDR Enhanced
Housing	IP66, IK10	IP67, IK10	IP66, IK10	IP66, IK10
Power Input	PoE	PoE (MD8562) DC 12V (MD8562D)	PoE DC 12V	PoE Plus DC 12V
Connectors	RJ45, M12 (Optional)	RJ45, M12 (Optional)	RJ45	RJ45
Dimensions	129 (D) x 107 (W) x 54 (H) mm	130 (D) x 107 (W) x 47 (H) mm	Ø 145 x 47 mm	Ø 160 x 51 mm

	Industrial PoE Switches				
	 AW-IHT-0500	 AW-IHT-0501	 AW-IHT-0502	 AW-IHT-0600	 AW-IHT-0601
Short Highlight	Industrial 4xFE PoE + 1xFE Switch	Industrial 4xFE PoE + 1xFE SC Multi-Mode 2KM Switch	Industrial 4xFE PoE + 1xFE SC Single-Mode 30KM Switch	Industrial 4xGE PoE + 1xGE Combo + 1xGE SFP Switch	Industrial 4xGE PoE + 1xGE Combo + 1xGE SFP Switch
Fast Ethernet (RJ45)	5	4	4	-	-
Fast Ethernet (Fiber)	-	SC Multi-mode 2 km	SC Single-mode 30 km	-	-
Gigabit Ethernet (RJ45)	-	-	-	5	5
Gigabit Ethernet (SFP)	-	-	-	2	2
Number of PoE Out Ports	4	4	4	4	4
Max. PoE Output Power/ per Port	30 W	30 W	30 W	30 W	30 W
Power Input	Redundant Dual 44V-56V DC Power Input Removable Terminal Block	Redundant Dual 44V-56V DC Power Input Removable Terminal Block	Redundant Dual 44V-56V DC Power Input Removable Terminal Block	Redundant Dual 44V-56V DC Power Input Removable Terminal Block	Redundant Dual 12V-56V DC Power Input Removable Terminal Block



Transport, a Part of Life that Needs Security

Transportation is a vital part of everyday life for the modern individual. As the use of mass transportation increases, so does the need for comprehensive surveillance systems that ensure the safety of passengers and increase overall efficiency. VIVOTEK offers ideal solutions that are compliant with industrial standards, such as EN50155, for railway applications.





EN50155

VIVOTEK Provides Dedicated Solutions for Railway Systems

The variety of environments and conditions encompassed by the railway sector is vast—outdoor and indoor spaces; wide-open and constrained areas; low-light and brightly lit; day and night – railways cover every conceivable operating environment. In view of this situation, VIVOTEK has developed a broad range of solutions, including high-performance network cameras and industrial switches. All of devices are compliant with the EN50155 standard.



Front and Rear Facing



MD8531H

- 30 fps @ 1280x960
- WDR Pro 120dB
- Video Rotation
- Two-way Audio



Pantograph



MD8531H

- 30 fps @ 1280x960
- WDR Pro 120dB
- Vandal-proof IK10 Housing
- Weather-proof IP66 Housing



Carriage Interior



MD8562/62D

- 30 fps @ 1920x1080
- FOV: 110° (H), 82° (V)
- Video Rotation
- One-way Audio
- Compact Size
- Vandal-proof IK10 Housing
- Tampering Detection



Carriage Exterior



MD8531H

- 30 fps @ 1280x960
- WDR Pro 120dB
- Video Rotation
- Vandal-proof IK10 Housing
- Weather-proof IP66 Housing



MD8562/62D

- 30 fps @ 1920x1080
- FOV: 110° (H), 82° (V)
- Video Rotation
- Vandal-proof IK10 Housing
- Weather-proof IP67 Housing



Driver Car



Industrial Switch Series

- 4x FE/GE PoE Ports
- Operating Temperature:
-40°C ~ 75°C (-40°F ~ 167°F)
- Redundant Power Input for Backup
- 24V Alarm Relay Output
- Compact Size



FE8181V

- 5 MP CMOS Sensor
- 360° Surround View
- 10M IR
- Compact Size



FE8174V/FE8181V

- 5 MP CMOS Sensor
- 180° Panoramic View
- 360° Surround View
- 10M IR (FE8181V)
- Compact Size
- Two-way Audio
- Vandal-proof IK10 Housing
- Tampering Detection